

## TECHNICAL SHEET



# AGUAPLAST®

## Woodfiller

### Waterborne Flexible Fibreglass Reinforced Wood Filler

- Copes with Up to 20% Wood Dilatation
- Fibreglass Reinforced Against Cracking
- Minimum Shrinkage

#### Properties and benefits

- Flexible: copes with up to 20% movement in wood.
- Fibreglass reinforced: no cracking due to temperature changes.
- Good filling capacity. Minimum shrinkage.
- Superb bond strength on wood and derivatives. Solvent free.
- Dries quickly in 2 hours. Very easy to sand. Can be painted or varnished once dry.

#### Areas of application

Interior and exterior repairs on wood:

- Filling and smoothing of wood pores and grain.
- Repairing pile worm.
- Smoothing and repairing holes, fissures and cracks on wood.

#### Substrate preparation and application

##### 1. Substrate

Wood must be clean, dry, and free of dust, grease or wax. Metallic parts must be protected against rust. Do not apply on humid wood.

##### 2. Application

Shake the tube before applying the product. Remove cap and cut top from nozzle. Apply two or

more layers to fill deep holes. Sand and overpaint (varnish, enamel, wood stain) after complete drying.

##### 3. Tools

Spatula. Clean tools with water.

##### 4. Storage

Expel the air out from the tube and close the cap properly. Store away from frost and humidity.

#### Technical Data

Product	Characteristics	Application
Packing	Tube 125 ml	Temperature 5° to 30°C
Form	Ready to use putty	Open time No limit
Colour	10 different colours available: neutral white, oak, mahogany, pine, walnut, teak, cherry, beech, sapele & wenge.	Maximum coat 5 mm
Storage	Close/seal properly. Keep away from humidity and extreme temperatures	Drying time 1 – 4 hours, depending on coat thickness, support nature and temperature and humidity conditions
Technical		On dry film, with any type of paint, varnish or enamel
Binder	Acrylic polymers	Clean excess with a soak cloth.
Diluent	Water	Clean tools with water immediately after use.
Density	Approximately 1,45 gr/cm3	
Disposal		
For information about disposal procedure and protection, refer to the corresponding Safety Data Sheet.		

#### General Notes

The details given in this information sheet are product descriptions. It is general information from our experience and tests and does not intend to be representative of the use of the products in specific situations. No claims for

replacements may arise from these details. If required, please contact our Technical Services Department. This form is provisional and is subject to changes without previous notice.

